

+86 13671515994
zyx@jetedge-cutting.com

Room 303, Unit 101, Building 1, Lane 388, Puwang Road,
Minhang District, Shanghai, China

<http://www.jetedge-cutting.com/>

JetEdge
CUTTING TOOLS

Shanghai JetEdge Cutting Tools Co., Ltd.
上海捷刃切削工具有限公司

2026

JetEdge
CUTTING TOOLS

CUTTING TOOL CATALOGUE

Shanghai JetEdge Cutting Tools Co., Ltd.
上海捷刃切削工具有限公司

<http://www.jetedge-cutting.com/>

CUTTING TOOL CATALOGUE

- Turning Inserts
- Threading tools
- Grooving inserts
- Milling tools



JetEdge
CUTTING TOOLS

Shanghai JetEdge Cutting Tools Co., Ltd.
上海捷刃切削工具有限公司



目录

A

通用车削刀片

■ ISO 车削刀片型号识别系统	A01-A02
■ 牌号应用范围 & CN 刀片	A03-A06
■ SN/TN 刀片	A07-A10
■ WN 刀片	A11-A12
■ CC/DC 刀片	A13-A14
■ SC/TC/VB 刀片	A15-A18
■ 常见问题与解决方案	A19-A20

B

螺纹加工刀片

■ 型号识别系统 & 螺纹类型	B01-B02
■ 60° / 55° 通用螺纹刀片	B03-B04
■ ISO 公制螺纹 & 惠氏螺纹	B05-B06
■ NPT & BSPT 管螺纹	B07-B10

C

切槽与切断刀片

■ MGMN/ MRMN /TDJ切槽刀片	C01-C02
■ TDC/TDT/TDXU切槽刀片	C03-C04
■ KNMR 切槽刀片	C05
■ TGF / GBA 浅槽刀片	C06

D

铣削刀具

■ ISO 铣削刀片型号表示方法	D01-D02
■ 方肩铣削	D03-D06
■ 仿形铣削 & 圆刀片铣削	D07-D09
■ 面铣 & 双面铣削	D10-D12
■ 高进给铣削	D13-D15
■ 端铣 & 周边铣削	D16-D17
■ 木工铣削 & 特殊铣削	D18



ISO 车削刀片型号识别系统

C
1

N
2

M
3

G
4


12
5

04
6


08
7

TM
8

1 形状 Shape




2 后角 Clearance angle



5 刀片形状 Shape of blades


Simbolo								Inch	IC
									
Metricoo									d (mm)
03	04	03	06	03	-	02	1.2 (5)	3.97	
04	05	04	08	04	08	S3	1.5 (6)	4.76	
05	06	05	09	05	09	03	1.8 (7)	5.56	
-	-	-	-	06	-	-	-	6.00	
06	07	06	11	06	11	04	2	6.35	
08	09	07	13	07	13	05	2.5	7.94	
-	-	-	-	08	-	-	-	8.00	
09	11	09	16	09	16	06	3	9.525	
-	-	-	-	10	-	-	-	10.00	
11	13	11	19	11	19	07	3.5	11.11	
-	-	-	-	12	-	-	-	12.00	
12	15	12	22	12	22	08	4	12.70	
14	17	14	24	14	24	09	4.5	14.29	
16	19	15	27	15	27	10	5	15.875	
-	-	-	-	16	-	-	-	16.00	
17	21	17	30	17	30	11	5.5	17.46	
19	23	19	33	19	33	13	6	19.05	
-	-	-	-	20	-	-	-	20.00	
22	27	22	38	22	38	15	7	22.225	
-	-	-	-	25	-	-	-	25.00	
25	31	25	44	25	44	17	8	25.40	
32	38	31	54	31	54	21	10	31.75	
-	-	-	-	32	-	-	-	32.00	

6 刀片厚度 Thickness of blades



Simbolo		Altura de filo de corte (t)	
Metric	Inch	mm	Inch
01	1 (2)	1.59	1/16
T0	1.125	1.79	9/128
T1	1.2	1.98	5/64
02	1.5 (3)	2.38	3/32
T2	1.75	2.78	7/64
03	2	3.18	1/8
T3	2.5	3.97	5/32
04	3	4.76	3/16
05	3.5	5.56	7/32
06	4	6.35	1/4
07	5	7.94	5/16
09	6	9.52	3/8
11	7	11.11	7/16
12	8	12.70	1/2

3 公差 Tolerance



Class	d	m	t
A	±0.025	±0.005	±0.025
C	±0.025	±0.013	±0.025
H	±0.013	±0.013	±0.025
E	±0.025	±0.025	±0.025
G	±0.025	±0.025	±0.13
J	±0.05~±0.15	±0.005	±0.025
K	±0.05~±0.15	±0.013	±0.025
L	±0.05~±0.15	±0.025	±0.025
M	±0.05~±0.15	±0.08~±0.20	±0.13
N	±0.05~±0.15	±0.08~±0.18	±0.025
U	±0.08~±0.25	±0.13~±0.38	±0.13


Tolerancia en clase C, H, R, T, W (Caso Excepcional)

d	Tolerancia on d		Tolerancia on m	
	J, K, L, M, N	U	M, N	U
6.35	±0.05	±0.08	±0.08	±0.13
9.525	±0.05	±0.08	±0.08	±0.13
12.7	±0.08	±0.13	±0.13	±0.20
15.875	±0.10	±0.18	±0.15	±0.27
19.05	±0.10	±0.18	±0.15	±0.27
25.4	±0.13	±0.25	±0.18	±0.38

Tolerancia en clase D (Caso Excepcional)

d	Tolerancia on d	Tolerancia on m
6.35	±0.05	±0.11
9.525	±0.05	±0.11
12.7	±0.08	±0.15
15.875	±0.10	±0.18
19.05	±0.10	±0.18

4 紧固方式 Seleccion transversal del inserto



7 刀尖圆弧代号 Arc code of tool tip



Simbolo		Radio de Punta	
Metric	Inch	Metric	Inch
003	0.1	0.03	0.0012
005	0.13	0.05	0.002
01	0.2	0.1	0.004
02	0.5	0.2	0.008
04	1	0.4	1/64
08	2	0.8	1/32
12	3	1.2	3/64
16	4	1.6	1/16
20	5	2.0	5/64
24	6	2.4	3/32
28	7	2.8	7/64
32	8	3.2	1/8
00	-	Placa redondo (Inch)	
M0	-	Placa redondo (Métrico)	

8 断屑槽型 Code of chip breaker type





■ 牌号应用范围

ISO使用 ISO Use		普通车削 Turning		螺纹 Threading		切断切槽 Parting and Grooving		ISO
工件材料 Workpiece materials	ISO代号 ISO Code	涂层 Coating		涂层 Coating		涂层 Coating		
		CVD	PVD	CVD	PVD	CVD	PVD	
P 钢件 Steel	P01	JE8015P			JE7015P		JE7015P	P01
	P10	JE8020P			JE7025P		JE7025P	P10
	P20	JE8025P						P20
	P30	JE8035P						P30
	P40							P40
M 不锈钢 Stainless Steel	M01							M01
	M10		JE6015M		JE6015M		JE6015M	M10
	M20		JE6025M		JE6025M		JE6025M	M20
	M30		JE6035M		JE6035M		JE6035M	M30
	M40							M40
K 铸铁 Cast Iron	K01	JE4015K	JE4015K	JE4015K	JE4015K	JE4015K	JE4015K	K01
	K10	JE4025K	JE4025K	JE4025K	JE4025K	JE4025K	JE4025K	K10
	K20							K20
	K30							K30
N 有色金属 Non-Ferrous Metal	N01							N01
	N10							N10
	N20							N20
	N30							N30
S 钛合金 耐热合金 Titanium Alloy Heat Resisting Alloy	S01							S01
	S10		JE5015S		JE5015S		JE5015S	S10
	S20		JE5025S		JE5025S		JE5025S	S20
	S30							S30
H 高硬度材料 High Strength Material	H01							H01
	H10							H10
	H20							H20
	H30							H30

K series grades are available with CVD / PVD coating depending on machining conditions.
K 系列可根据工况选择 CVD 或 PVD 涂层。

■ 菱形 80°
(负角)



		Workpiece material		Continuous cutting				General cutting			Interrupted cutting							
				Steel				Stainless steel			Cast iron		Non-ferrous metal		Heat resistant alloy Ti alloy			
				Steel				Stainless steel			Cast iron		Non-ferrous metal		Heat resistant alloy Ti alloy			
Inserts shape	Type	Dimensions(mm)					Coating/Grade											
		I.C	L	S	d	r	CVD				PVD		CVD		PVD			
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S	
Finishing 精加工		CNMA120408	12.7	12.9	4.76	5.16	0.8								○	●		
		CNMA120412	12.7	12.9	4.76	5.16	1.2								○	●		
		CNMG120404-TFA	12.7	12.9	4.76	5.16	0.4	○	○	●	○							
		CNMG120408-TFA	12.7	12.9	4.76	5.16	0.8	○	○	●	○							
		CNMG120412-TFA	12.7	12.9	4.76	5.16	1.2	○	○	●	○							
Semi-finishing 半精加工		CNMG120404-TFB	12.7	12.9	4.76	5.16	0.4	○	○	●	○							
		CNMG120408-TFB	12.7	12.9	4.76	5.16	0.8	○	○	●	○							
		CNMG120404-TMD	12.7	12.9	4.76	5.16	0.4								○	●		
		CNMG120408-TMD	12.7	12.9	4.76	5.16	0.8								○	●		
		CNMG120412-TMD	12.7	12.9	4.76	5.16	1.2								○	●		
Roughing 粗加工		CNMG120404-TMB	12.7	12.9	4.76	5.16	0.4					○	●	○				
		CNMG120408-TMB	12.7	12.9	4.76	5.16	0.8					○	●	○				
		CNMG120412-TMB	12.7	12.9	4.76	5.16	1.2					○	●	○				
		CNMG120404-TMC	12.7	12.9	4.76	5.16	0.4					○	●	○				
		CNMG120408-TMC	12.7	12.9	4.76	5.16	0.8					○	●	○				
		CNMG120412-TMC	12.7	12.9	4.76	5.16	1.2					○	●	○				
Roughing 粗加工		CNMG120404-TRB	9.525	12.9	4.76	5.16	0.4	○	○	●	○							
		CNMG120408-TRB	9.525	12.9	4.76	5.16	0.8	○	○	●	○							
		CNMG120412-TRB	9.525	12.9	4.76	5.16	1.2	○	○	●	○							
		CNMG120404-TMA	12.7	12.9	4.76	5.16	0.4	○	○	●	○							
		CNMG120408-TMA	12.7	12.9	4.76	5.16	0.8	○	○	●	○							
		CNMG120412-TMA	12.7	12.9	4.76	5.16	1.2	○	○	●	○							
Roughing 粗加工		CNMG120404-TRA	12.7	12.9	4.76	5.16	0.4								○	●		
		CNMG120408-TRA	12.7	12.9	4.76	5.16	0.8								○	●		
		CNMG120412-TRA	12.7	12.9	4.76	5.16	1.2								○	●		
		CNMG120416-TRA	12.7	12.9	4.76	5.16	1.6								○	●		

● Featured grade
主推牌号

○ Optional grade
可选牌号





菱形 80°
(负角)



80°菱形
负角
带孔

Inserts shape	Type	Dimensions(mm)					Coating/Grade							
		I.C	L	S	d	r	CVD				PVD			
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K
粗加工	CNMG120408L-TMF	12.7	12.9	4.76	5.16	0.8	○	○	●	○				
	CNMG120408R-TMF	12.7	12.9	4.76	5.16	0.8	○	○	●	○				
粗加工	CNMG160608-TRC	15.875	16.1	6.35	6.35	0.8	○	○	●	○				
	CNMG160612-TRC	15.875	16.1	6.35	6.35	1.2	○	○	●	○				
	CNMG160616-TRC	15.875	16.1	6.35	6.35	1.6	○	○	●	○				
	CNMG190608-TRC	19.05	19.34	6.35	7.94	0.8	○	○	●	○				
	CNMG190612-TRC	19.05	19.34	6.35	7.94	1.2	○	○	●	○				
	CNMG190616-TRC	19.05	19.34	6.35	7.94	1.6	○	○	●	○				
重载车刀片	CNMM190624-TRC	19.05	19.34	6.35	7.94	0.8	○	○	●	○				
	CNMM190612-TRC	19.05	19.34	6.35	7.94	0.8	○	○	●	○				
	CNMM190616-TRC	19.05	19.34	6.35	7.94	0.8	○	○	●	○				
	CNMM190624-TRC	19.05	19.34	6.35	7.94	0.8	○	○	●	○				
	CNMM250624-TRC	12.7	12.9	4.76	5.16	0.8	○	○	●	○				
	CNMM190612-THA	19.05	12.9	4.76	5.16	0.4	○	○	●	○				

● Featured grade 主推牌号 ○ Optional grade 可选牌号

菱形 55°
(负角)



55°菱形
负角
带孔

Inserts shape	Type	Dimensions(mm)					Coating/Grade							
		I.C	L	S	d	r	CVD				PVD			
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K
半精加工	DNMA150408	12.7	15.5	4.76	5.08	0.8								○ ●
	DNMA150412	12.7	15.5	4.76	5.08	1.2								○ ●
	DNMA150608	12.7	15.5	6.35	5.08	0.8								○ ●
	DNMA150412	12.7	15.5	6.35	5.08	1.2								○ ●
	DNMA150416	12.7	15.5	6.35	5.08	1.6								○ ●
	DNMG150404-TMB	12.7	15.5	4.76	5.16	0.4					○ ● ○			
粗加工	DNMG150408-TMB	12.7	15.5	4.76	5.16	0.8					○ ● ○			
	DNMG150408-TRA	12.7	15.5	4.76	5.16	0.8								○ ●
	DNMG150608-TRA	12.7	15.5	6.35	5.16	0.8								○ ●
	DNMG150612-TRA	12.7	15.5	6.35	5.16	1.2								○ ●
	DNMG150616-TRA	12.7	15.5	6.35	5.16	1.6								○ ●
	DNMG150404-TMA	12.7	15.5	4.76	5.16	0.4	○ ○ ● ○							
	DNMG150408-TMA	12.7	15.5	4.76	5.16	0.8	○ ○ ● ○							
	DNMG150412-TMA	12.7	15.5	4.76	5.16	1.2	○ ○ ● ○							
	DNMG150604-TMA	12.7	15.5	6.35	5.16	0.4	○ ○ ● ○							
	DNMG150608-TMA	12.7	15.5	6.35	5.16	0.8	○ ○ ● ○							

● Featured grade 主推牌号 ○ Optional grade 可选牌号

90°正方形
(负角)



■ **60°正三角形**
(负角)

[illegible]


● Featured grade
主推牌号

○ Optional grade
可选牌号

60°正三角形
(负角)

TN

60°正三角形
负角
带孔



Workpiece material	连续切削 Continuous cutting				一般工况 General cutting			断续切削 Interrupted cutting		
	P Steel	M Stainless steel	K Cast iron	N Non-ferrous metal	S Heat resistant alloy	Ti alloy				
P Steel	●	●	●	●	●	●	●	●	●	●
M Stainless steel	●	●	●	●	●	●	●	●	●	●
K Cast iron	●	●	●	●	●	●	●	●	●	●
N Non-ferrous metal	●	●	●	●	●	●	●	●	●	●
S Heat resistant alloy	●	●	●	●	●	●	●	●	●	●
Ti alloy	●	●	●	●	●	●	●	●	●	●

Inserts shape	Type	Dimensions(mm)					Coating/Grade							
		I.C	L	S	d	r	CVD				PVD			
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K
粗加工 Roughing	TNMG160408-TRA	9.525	16.5	4.76	3.81	0.8								○
	TNMG160412-TRA	9.525	16.5	4.76	3.81	1.2								○
	TNMG160416-TRA	9.525	16.5	4.76	3.81	1.6								○
	TNMG220408-TRA	12.7	22	4.76	5.16	0.8								○
	TNMG220412-TRA	12.7	22	4.76	5.16	1.2								○
	TNMG220416-TRA	12.7	22	4.76	5.16	1.6								○
	TNMG160404-TMA	9.525	16.5	4.76	3.81	0.4	○	○	●	○				
	TNMG160408-TMA	9.525	16.5	4.76	3.81	0.8	○	○	●	○				
	TNMG160412-TMA	9.525	16.5	4.76	3.81	1.2	○	○	●	○				
	TNMG160404L-TMF	9.525	16.5	4.76	3.81	0.4	○	○	●	○				
半精加工 Semi-finishing	TNMG160408L-TMF	9.525	16.5	4.76	3.81	0.8	○	○	●	○				
	TNMG160408R-TMF	9.525	16.5	4.76	3.81	0.8	○	○	●	○				
	TNRW160302	9.525	16.5	3.81	4.4	0.2					○	●	○	
	TNRA160402	9.525	16.5	4.76	3.81	0.2					○	●	○	
	TNRG160402-TAB	9.525	16.5	4.76	3.81	0.2					○	●	○	


● Featured grade
主推牌号

○ Optional grade
可选牌号

35°菱形
(负角)

VN

35°菱形
负角
带孔



Workpiece material	连续切削 Continuous cutting				一般工况 General cutting			断续切削 Interrupted cutting		
	P Steel	M Stainless steel	K Cast iron	N Non-ferrous metal	S Heat resistant alloy	Ti alloy				
P Steel	●	●	●	●	●	●	●	●	●	●
M Stainless steel	●	●	●	●	●	●	●	●	●	●
K Cast iron	●	●	●	●	●	●	●	●	●	●
N Non-ferrous metal	●	●	●	●	●	●	●	●	●	●
S Heat resistant alloy	●	●	●	●	●	●	●	●	●	●
Ti alloy	●	●	●	●	●	●	●	●	●	●

Inserts shape	Type	Dimensions(mm)					Coating/Grade							
		I.C	L	S	d	r	CVD				PVD			
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K
精加工 Finishing	VNMA160404	9.525	16.6	4.76	3.8	0.4								○
	VNMA160408	9.525	16.6	4.76	3.8	0.8								○
	VNMG160404-TFB	9.525	16.6	4.76	3.8	0.4	○	○	●	○				
	VNMG160408-TFB	9.525	16.6	4.76	5.16	0.8	○	○	●	○				
	VNMG160404-TMD	12.7	16.6	4.76	5.16	0.4								○
	VNMG160408-TMD	12.7	16.6	4.76	5.16	0.8								○
	VNMG160412-TMD	12.7	16.6	4.76	5.16	1.2								○
	VNMG160404-TMB	9.525	16.6	4.76	3.8	0.4					○	●	○	
	VNMG160408-TMB	9.525	16.6	4.76	3.8	0.8					○	●	○	
	VNMG160404-TMC	9.525	16.6	4.76	3.8	0.4					○	●	○	
半精加工 Semi-finishing	VNMG160408-TMC	9.525	16.6	4.76	3.8	0.8					○	●	○	
	VNMG160404-TRB	9.525	16.6	4.76	3.8	0.4	○	○	●	○				
	VNMG160408-TRB	9.525	16.6	4.76	3.8	0.8	○	○	●	○				
	VNMG160412-TRB	9.525	16.6	4.76	3.8	1.2	○	○	●	○				
	VNMG160408-TRA	9.525	16.6	4.76	3.8	0.8								○
	VNMG160412-TRA	9.525	16.6	4.76	3.8	1.2								○
	VNMG160404-TMA	9.525	16.6	4.76	3.8	0.4	○	○	●	○				
	VNMG160408-TMA	9.525	16.6	4.76	3.8	0.8	○	○	●	○				
	VNMG160412-TMA	9.525	16.6	4.76	3.8	1.2	○	○	●	○				
	VNMG160402-TAB	9.525	16.6	4.76	3.81	0.2								○

● Featured grade
主推牌号

○ Optional grade
可选牌号



80°六角形
(负角)



80°六角形
负角
带孔

		连续切削 Continuous cutting		一般工况 General cutting		断续切削 Interrupted cutting												
Workpiece material	P	Steel	●	→	→	→	→											
	M	Stainless steel						●	→	→								
	K	Cast iron												●	→			
	N	Non-ferrous metal																
	S	Heat resistant alloy Ti alloy														●	→	
		Dimensions(mm)						Coating/Grade										
Inserts shape	Type						CVD		PVD			CVD		PVD				
		I.C	L	S	d	r	JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S	
半精加工 Semi-finishing		WNMA080408	12.7	8.7	4.76	5.16	0.8								○	●		
	WNMA080412	12.7	8.7	4.76	5.16	1.2									○	●		
精加工 Finishing		WNMG080404-TFC	12.7	8.7	4.76	5.16	0.4					○	●	○				
	WNMG080408-TFC	12.7	8.7	4.76	5.16	0.8					○	●	○					
	WNMG080412-TFC	12.7	8.7	4.76	5.16	1.2					○	●	○					
		WNMG080404-TFA	12.7	8.7	4.76	5.16	0.4	○	○	●	○							
	WNMG080418-TFA	12.7	8.7	4.76	5.16	1.8	○	○	●	○								
	WNMG080412-TFA	12.7	8.7	4.76	5.16	1.2	○	○	●	○								
		WNMG080404-TFB	12.7	8.7	4.76	5.16	0.4	○	○	●	○							
	WNMG080408-TFB	12.7	8.7	4.76	5.16	0.8	○	○	●	○								
半精加工 Semi-finishing		WNMG080404-TMD	12.7	8.7	4.76	5.16	0.4								○	●		
	WNMG080408-TMD	12.7	8.7	4.76	5.16	0.8									○	●		
	WNMG080412-TMD	12.7	8.7	4.76	5.16	1.2									○	●		
		WNMG080404-TMB	12.7	8.7	4.76	5.16	0.4					○	●	○				
	WNMG080408-TMB	12.7	8.7	4.76	5.16	0.8					○	●	○					
	WNMG080412-TMB	12.7	8.7	4.76	5.16	1.2					○	●	○					
		WNMG080404-TMC	12.7	8.7	4.76	5.16	0.4					○	●	○				
	WNMG080408-TMC	12.7	8.7	4.76	5.16	0.8					○	●	○					
	WNMG080412-TMC	12.7	8.7	4.76	5.16	1.2					○	●	○					
		WNMG080404-TRB	12.7	8.7	4.76	5.16	0.4	○	○	●	○							
WNMG080408-TRB	12.7	8.7	4.76	5.16	0.8	○	○	●	○									
粗加工 Roughing		WNMG080412-TRB	12.7	8.7	4.76	5.16	1.2	○	○	●	○							
	WNMG080404-TRA	12.7	8.7	4.76	5.16	0.4								○	●			
	WNMG080408-TRA	12.7	8.7	4.76	5.16	0.8								○	●			
	WNMG080412-TRA	12.7	8.7	4.76	5.16	1.2								○	●			

● Featured grade
主推牌号

○ Optional grade
可选牌号



80°六角形
(负角)



80°六角形
负角
带孔

		连续切削 Continuous cutting				一般工况 General cutting			断续切削 Interrupted cutting							
Workpiece material	P	Steel	●	→	→	→										
	M	Stainless steel					●	→	→							
	K	Cast iron											●	→		
	N	Non-ferrous metal														
	S	Heat resistant alloy Ti alloy													●	→

Inserts shape	Type	Dimensions(mm)					Coating/Grade										
		I.C	L	S	d	r	CVD				PVD			CVD		PVD	
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
粗加工 Roughing		WNMG080404-TMA	12.7	8.7	4.76	5.16	0.4	○	○	●	○						
		WNMG080408-TMA	12.7	8.7	4.76	5.16	0.8	○	○	●	○						
		WNMG080412-TMA	12.7	8.7	4.76	5.16	1.2	○	○	●	○						
		WNMG080404L-TMF	12.7	8.7	4.76	5.16	0.4	○	○	●	○						
		WNMG080404R-TMF	12.7	8.7	4.76	5.16	0.4	○	○	●	○						
		WNMG080408L-TMF	12.7	8.7	4.76	5.16	0.8	○	○	●	○						
		WNMG080408R-TMF	12.7	8.7	4.76	5.16	0.8	○	○	●	○						

● Featured grade
主推牌号

○ Optional grade
可选牌号



80°菱形
(正角)



							Steel Stainless steel Cast iron Non-ferrous metal Heat resistant alloy Ti alloy		连续切削 Continuous cutting		一般工况 General cutting		断续切削 Interrupted cutting				
Inserts shape	Type	Dimensions(mm)					Coating/Grade										
		I.C	L	S	d	r	CVD				PVD		CVD		PVD		
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
 精加工	CCMT060202	6.35	6.45	2.38	2.8	0.2	○	○	●	○	○	●	○	○	●	○	●
	CCMT060204	6.35	6.45	2.38	2.8	0.4	○	○	●	○	○	●	○	○	●	○	●
	CCMT060208	6.35	6.45	2.38	2.8	0.8	○	○	●	○	○	●	○	○	●	○	●
	CCMT09T304	9.525	9.67	3.97	4.4	0.4	○	○	●	○	○	●	○	○	●	○	●
	CCMT09T308	9.525	9.67	3.97	4.4	0.8	○	○	●	○	○	●	○	○	●	○	●
	CCMT120404	12.7	12.9	4.76	5.5	0.4	○	○	●	○	○	●	○	○	●	○	●
	CCMT120408	12.7	12.9	4.76	5.5	0.8	○	○	●	○	○	●	○	○	●	○	●
	CCRT060202K	6.35	6.45	2.38	2.8	0.2	○	○	●	○	○	●	○	○	●	○	●
	CCRT09T302K	9.525	9.67	3.97	4.4	0.2	○	○	●	○	○	●	○	○	●	○	●
 半精加工	CCRT060202-TFD	6.35	6.45	2.38	2.8	0.2	○	○	●	○	○	●	○	○	●	○	●
	CCRT09T302-TFD	9.525	9.67	3.97	4.4	0.2	○	○	●	○	○	●	○	○	●	○	●
	CCRT09T302-TAA	9.525	9.67	3.97	4.4	0.2	○	○	●	○	○	●	○	○	●	○	●
							○	○	●	○	○	●	○	○	●	○	●
 精加工	CCRW030101	3.5	3.55	1.4	1.9	0.1	○	○	●	○	○	●	○	○	●	○	●
	CCRW040101	4.3	4.37	1.8	2.3	0.1	○	○	●	○	○	●	○	○	●	○	●
	CCRW060202	6.35	6.45	2.38	2.8	0.2	○	○	●	○	○	●	○	○	●	○	●
	CCRW09T302	9.525	9.67	3.97	4.4	0.4	○	○	●	○	○	●	○	○	●	○	●

Featured grade
主推牌号

Optional grade
可选牌号

● Featured grade 主推牌号 ○ Optional grade 可选牌号

55°菱形
(正角)



		Workpiece material		Continuous cutting		一般工况 General cutting		断续切削 Interrupted cutting											
				P Steel		M Stainless steel		K Cast iron		N Non-ferrous metal		S Heat resistant alloy Ti alloy							
Inserts shape	Type	Dimensions(mm)					Coating/Grade												
							CVD				PVD			CVD		PVD			
		I.C	L	S	d	r	JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S		
精加工 Finishing		DCMT070204	6.35	6.45	2.38	2.8	0.2	○	○	●	○	○	●	○	○	●	○	●	
		DCMT070208	6.35	6.45	2.38	2.8	0.4	○	○	●	○	○	●	○	○	●	○	●	
		DCMT11T304	6.35	6.45	2.38	2.8	0.8	○	○	●	○	○	●	○	○	●	○	●	
		DCMT11T308	9.525	9.67	3.97	4.4	0.4	○	○	●	○	○	●	○	○	●	○	●	
半精加工 Semi-finishing		DCMT070202-TME	9.525	9.67	3.97	4.4	0.8	○	○	●	○	○	●	○	○	●	○	●	
		DCMT070204-TME	12.7	12.9	4.76	5.5	0.4	○	○	●	○	○	●	○	○	●	○	●	
		DCMT070208-TME	12.7	12.9	4.76	5.5	0.8	○	○	●	○	○	●	○	○	●	○	●	
		DCMT11T304-TME	6.35	6.45	2.38	2.8	0.2	○	○	●	○	○	●	○	○	●	○	●	
精加工 Finishing		DCMT11T308-TME	9.525	9.67	3.97	4.4	0.2	○	○	●	○	○	●	○	○	●	○	●	
		DCRT070202K	6.35	7.75	2.39	2.8	0.2	○	○	●	○	○	●	○	○	●	○	●	
		DCRT11T302K	9.525	11.6	2.39	4.4	0.2	○	○	●	○	○	●	○	○	●	○	●	
		DCRT070202-TFD	6.35	7.75	2.38	2.8	0.2	○	○	●	○	○	●	○	○	●	○	●	
		DCRT11T302-TFD	6.35	11.6	2.38	2.8	0.2	○	○	●	○	○	●	○	○	●	○	●	
		DCRT11T304-TFD	6.35	11.6	2.38	2.8	0.4	○	○	●	○	○	●	○	○	●	○	●	
半精加工 Semi-finishing		DCRT070202-TAA	6.35	7.75	2.38	2.8	0.2	○	○	●	○	○	●	○	○	●	○	●	
		DCRT11T302-TAA	6.35	11.6	2.38	2.8	0.2	○	○	●	○	○	●	○	○	●	○	●	
		DCRW070202	6.35	7.75	2.38	2.8	0.2	○	○	●	○	○	●	○	○	●	○	●	
半精加工 Semi-finishing		DCRW11T301	9.525	11.6	3.97	4.4	0.1	○	○	●	○	○	●	○	○	●	○	●	
		DCRW11T302	9.525	11.6	3.97	4.4	0.2	○	○	●	○	○	●	○	○	●	○	●	

● Featured grade 主推牌号 ○ Optional grade 可选牌号





90°正方形
(正角)




90°正方形
正角
带孔

							连续切削 Continuous cutting 一般工况 General cutting 断续切削 Interrupted cutting											
Workpiece material																		
P Steel																		
M Stainless steel																		
K Cast iron																		
N Non-ferrous metal																		
S Heat resistant alloy Ti alloy																		

Inserts shape	Type	Dimensions(mm)					Coating/Grade										
		I.C	L	S	d	r	CVD				PVD			CVD		PVD	
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
Finishing 精加工		SCMT09T304	9.525	9.525	3.97	4.4	0.4										
		SCMT09T308	9.525	9.525	3.97	4.4	0.8										
		SCMT120404	12.7	12.7	4.76	5.5	0.4										
		SCMT120408	12.7	12.7	4.76	5.5	0.8										
		SCRT09T302K	9.525	9.525	3.97	4.4	0.2										
		SCRW09T302	9.525	9.525	3.97	4.4	0.2										

● Featured grade 主推牌号
○ Optional grade 可选牌号

60°正三角形
(正角)



60°正三角形
正角
带孔

							连续切削 Continuous cutting 一般工况 General cutting 断续切削 Interrupted cutting										
Workpiece material P Steel M Stainless steel K Cast iron N Non-ferrous metal S Heat resistant alloy Ti alloy																	
Inserts shape	Type	Dimensions(mm)					Coating/Grade										
		I.C	L	S	d	r	CVD				PVD			CVD		PVD	
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
Finishing 精加工	TCMT090204	5.56	9.6	2.38	2.5	0.4	○	○	●	○	○	●	○	○	●	○	●
	TCMT090208	5.56	9.6	2.38	2.5	0.8	○	○	●	○	○	●	○	○	●	○	●
	TCMT110204	6.35	11	2.38	2.8	0.4	○	○	●	○	○	●	○	○	●	○	●
	TCMT110208	6.35	11	2.38	2.8	0.8	○	○	●	○	○	●	○	○	●	○	●
	TCMT16T304	9.525	165	3.97	4.4	0.4	○	○	●	○	○	●	○	○	●	○	●
	TCMT16T308	9.525	165	3.97	4.4	0.8	○	○	●	○	○	●	○	○	●	○	●
Semi-finishing 半精加工																	

● Featured grade 主推牌号
○ Optional grade 可选牌号







35°菱形
(正角)

VB

35°菱形
正角
带孔



Workpiece material	连续切削 Continuous cutting				一般工况 General cutting			断续切削 Interrupted cutting		
	P	M	K	N	S					
Steel	●	●	●	●	●					
Stainless steel		●	●		●					
Cast iron			●					●	●	
Non-ferrous metal										
Heat resistant alloy Ti alloy									●	●

Inserts shape		Type	Dimensions(mm)					Coating/Grade										
								CVD				PVD			CVD		PVD	
								JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
精加工 Finishing		VBMT110304	6.35	11.1	2.38	2.8	0.4	○	○	●	○	○	●	○	○	●	○	●
		VBMT110308	6.35	11.1	2.38	2.8	0.8	○	○	●	○	○	●	○	○	●	○	●
		VBMT160404	9.525	16.6	3.97	4.4	0.4	○	○	●	○	○	●	○	○	●	○	●
		VBMT160408	9.525	16.6	3.97	4.4	0.8	○	○	●	○	○	●	○	○	●	○	●
		VCRT110302K	6.35	11.1	3.18	2.8	0.2	○	○	●	○	○	●	○	○	●	○	●
		VCRT160402K	9.525	16.6	4.76	4.4	0.2	○	○	●	○	○	●	○	○	●	○	●
		VCRT110302-TFD	6.35	11.1	3.18	2.8	0.2	○	○	●	○	○	●	○	○	●	○	●
		VCRT110301-TAA	6.35	11.1	3.18	2.8	0.1	○	○	●	○	○	●	○	○	●	○	●
		VCRT110302-TAA	6.35	11.1	3.18	2.8	0.2	○	○	●	○	○	●	○	○	●	○	●
半精加工 Semi-finishing		VBRW110301	6.35	11.1	3.18	2.8	0.1	○	○	●	○	○	●	○	○	●	○	●
		VBRW110302	6.35	11.1	3.18	2.8	0.2	○	○	●	○	○	●	○	○	●	○	●
		VBRW160402	9.525	16.6	4.76	4.4	0.2	○	○	●	○	○	●	○	○	●	○	●
		VPRW110302	6.35	11.1	3.18	2.8	0.2	○	○	●	○	○	●	○	○	●	○	●

● Featured grade
主推牌号

○ Optional grade
可选牌号



常见问题与解决方案

选择条件 Selection condition			刀具材料选择 Selection of Tool material		切削条件 Cutting Condition	
			硬度更高的材料 Material with higher hardness	韧性好的材料 Material with good toughness	切削速度 cutting speed	进给 feeding
刀尖磨损过大 Too much wear for the knife point	加工中精度超标 Machining accuracy beyond standard	后刀面磨损增大 Flank wear increases	✓			
		切削条件不适合 Cutting condition is not suitable			↓	↑
表面精度恶化 Surface accuracy deterioration	表面质量差 Poor surface quality	刀具磨损增大、刀刃不够锋利 Tool wear increases and the blade is not sharp enough	✓		↓	
		切削刃缺损 Cutting edge defect		✓		↓
		切削刃几何形状不合适 Cutting edge geometry is not appropriate				
		切削条件不合适 Cutting condition is not suitable			↑	↓
		振动、发颤 Vibration and tremble		✓	↑↓	↓
		积屑瘤 built-up edge			↑	↑
发热 Heat	切削热的影响 Cutting heat effect	切削条件不合适 Cutting condition is not suitable			↓	
		切削刃几何形状不合适 Cutting edge geometry is not appropriate	✓			
尺寸精度差 Poor dimensional accuracy	加工中尺寸波动 Dimension fluctuation in machining	刀片精度不合适 The blade accuracy is not suitable				
		工件、刀具位置偏移 Work tool offset			↑	
刀具切削刃损伤 Cutting edge damage	后刀面、前刀面磨损增大 Wear increases on the back and front knife surfaces	后刀面磨损 The front edge wears	✓		↓	
		前刀面磨损 The back edge wears	✓		↓	↓
	微崩 Minor Tipping	振动、冲击 Vibration and impact		✓		↓
	积屑瘤 Built-up edge	工件硬度与刀具切削条件不适合 The hardness of the tool material is not suitable for cutting condition				↑
	热龟裂 Thermal cracking	工件材料的硬度与刀具材料和切削条件不适合 The hardness of the tool material is not suitable for cutting condition			↓	↓
	切削刃刀尖部分变形 Cutting edge deformation	在断续切削大进给时发生 Occurs when intermittent cutting in large feeding	✓			↓
切屑控制 Cutting control	长切屑缠绕 long cutting chips, winding	材料、切削条件不合适 Tool material is not suitable for cutting condition		✓		↓
		切削条件不合适 Cutting condition is not suitable			↓	↑
	切屑太短，导致飞溅 Short cutting chips, causing splash	刀刃几何形状不合适 Cutting edge geometry is not appropriate				
		切削条件不合适 Cutting condition is not suitable				↓
毛刺、塌边 Burr, Collapse	钢、铝，产生毛刺 Steel and aluminum, burrs	切削条件不合适 Cutting condition is not suitable			↑	↓
		刀具磨损、几何形状不合适 Cutting tool wears and Cutting edge geometry is not appropriate	✓			
	铸铁，塌边 Cast iron, collapse	切削条件不合适 Cutting condition is not suitable			↓	↑
		刀具磨损、几何形状不合适 Cutting tool wears and Cutting edge geometry is not appropriate	✓			
	软钢，毛边 Mild steel, burrs	切削条件不合适 Cutting condition is not suitable				↓
		刀具磨损、几何形状不合适 Cutting tool wears and Cutting edge geometry is not appropriate	✓			

✓ 这个因素需要重点检查或调整
This factor requires careful examination or adjustment.

↑ 建议增加这个参数
It is suggested to add this parameter.

↓ 建议降低这个参数
It is suggested to reduce this parameter.


切削条件 Cutting Condition		刀具形状 Shape of tool							机床装夹 Machine tool clamping		
切深 cutting depth	切削液 Cutting fluid	改变刀片槽型 Change chip breakers of the inserts	前角 front angle	刀尖圆弧半径 corner radius	主偏角 cutting edge angle	切削刃强度 cutting edge strength	提高刀片精度 Improve blade accuracy	提高刀具刚性 improve blade rigidity	工件刀柄装夹 Workpiece holder clamping	刀柄悬伸 Tool holder overhanging	动力、机床间隙 Power machine clearance
				↑							
							✓				
	✓		↑	↑		↓			✓	✓	✓
↓		✓		↑		↑					
		✓		↑		↓	✓				
↓	✓										
↓	✓	✓	↑	↓	↑	↓			✓	✓	✓
	✓	✓	↑			↓	✓				
		✓	↑			↓					
		✓	↑								
			↑			↓					
		✓	↑	↓	↑			✓	✓	✓	✓
		✓	↑								
↓		✓	↑	↓	↑						
	✓										
		✓		↓	↑						
↓	✓										
		✓		↑	↓						
	✓										
		✓	↑	↓	↑	↓					
↓											
		✓	↑	↑		↑		✓	✓	✓	✓

型号识别系统

16 **E** **R** **1.50** **ISO** **M** **HMC**
(1) (2) (3) (4) (5) (6) (7)


1 刀片尺寸 Inserts size

INSL (mm)	IC
06	3.97 mm = 5/32"
08	4.76 mm = 3/16"
11	6.35 mm = 1/4"
16	9.52 mm = 3/8"
22	12.70 mm = 1/2"
27	15.88 mm = 5/8"



2 应用 Application

E - External
I - Internal
VE - V-type



3 切削方向 Hand of tool

R - 右手 Right-hand
L - 左手 Left-hand
RL - 左右手 Right and left-hand

4 螺距 Pitch

全牙形 **Full profile**
数字范围 **Value by number**
0.35-9.0mm (Thread pitch)
72-2 TPI (Threads per inch)

4 螺距 Pitch

V牙形 **V-shaped teeth**
字母范围 **Range by letter**

	mm	TPI
	(Thread pitch)	(Threads per inch)

A	0.5-1.5mm	48-16
AG	0.5-3.0mm	48-8
G	1.75-3.0mm	14-8
N	3.5-5.0mm	7-5
Q	5.5-6.0mm	4.5-4
U	5.5-9.0mm	4.5-2.75

5 螺纹牙形 Thread standard

ISO
公制螺纹 - ISO metric
60°通用螺纹 - Partial profile 60°
55°通用螺纹 - Partial profile 55°
UN - American UN
统一协定螺纹
W - Whitworth
惠氏螺纹
NPT - NPT
美制锥管螺纹
BSPT - British BSPT
英制锥管螺纹
TR - Trapeze DIN103
标准梯形螺纹
ACME - ACME
美制梯形螺纹
STACME - Stub ACME
美制短齿梯形螺纹
RD - Round DIN403
消防食品机械圆螺纹
ABUT - American buttress
美制锯齿螺纹
SAGE - Sagengewinde DIN51
德标锯齿螺纹

6 类型 Type

M - Grinding
磨制
□ - Chipbreaker
断屑槽


7 牌号 Grades

螺纹类型

螺纹种类 call letters	公制	通用螺纹	通用螺纹	统一协定	惠氏	英制螺纹	美制螺纹
	IOS	60°	55°	UN	W	BSPT	NPT
螺纹形状 Description							
螺距 Pitch	mm	牙 / 英寸 Pitch/inch	牙 / 英寸 Pitch/inch	牙 / 英寸 Pitch/inch	牙 / 英寸 Pitch/inch	牙 / 英寸 Pitch/inch	牙 / 英寸 Pitch/inch
应用领域 Application	一般工业机械				燃气、水和管道螺纹		

螺纹种类 call letters	美制干密封螺纹	梯形螺纹	美制梯形螺纹	美制短锯齿 梯形螺纹	美制锯齿螺纹	德标锯齿螺纹	消防食品机械 圆螺纹
	NPTF	TR	ACME	STACME	ABUT	SAGE	RD
螺纹形状 Description							
螺距 Pitch	牙 / 英寸 Pitch/inch	mm	牙 / 英寸 Pitch/inch	牙 / 英寸 Pitch/inch	牙 / 英寸 Pitch/inch	mm	牙 / 英寸 Pitch/inch
应用领域 Application	燃气、水和 管道螺纹		机械传动				食品和 消防行业 管接头螺纹


60°通用 外螺纹



Inserts shape	Type	Pitch Range (mm)	Dimensions(mm)						Coated Cemented Carbide								
			PDY	PDX	RE	IC	S	D1	JE7015P	JE7025P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
	16ERAG60-HGA	0.5~3.0	1.1	1.5	0.08	9.525	3.47	4	○	●	○	●	○	○	●	○	●

● Featured grade 主推牌号 ○ Optional grade 可选牌号


55°通用 外螺纹



Inserts shape	Type	Pitch Range (TPI)	Dimensions(mm)						Coated Cemented Carbide								
			PDY	PDX	RE	IC	S	D1	JE7015P	JE7025P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
	16ERAG55-HGA	48-8	1.1	1.5	0.08	9.525	3.47	4	○	●	○	●	○	○	●	○	●

● Featured grade 主推牌号 ○ Optional grade 可选牌号


60°通用 内螺纹



Inserts shape	Type	Pitch Range (mm)	Dimensions(mm)						Recommended Grade								
			PDY	PDX	RE	IC	S	D1	JE7015P	JE7025P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
	16IRAG60-HGA	0.5~3.0	1.1	1.5	0.08	9.525	3.47	4	○	●	○	●	○	○	●	○	●

● Featured grade 主推牌号 ○ Optional grade 可选牌号


55°通用 内螺纹



Inserts shape	Type	Pitch Range (TPI)	Dimensions(mm)						Coated Cemented Carbide								
			PDY	PDX	RE	IC	S	D1	JE7015P	JE7025P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
	16IRAG55-HGA	48-8	1.1	1.5	0.08	9.525	3.47	4	○	●	○	●	○	○	●	○	●

● Featured grade 主推牌号 ○ Optional grade 可选牌号


ISO公制 外螺纹



Inserts shape	Type	Pitch Range (mm)	Dimensions(mm)						Coated Cemented Carbide							
			PDY	PDX	RE	IC	S	D1	JE7015P	JE7025P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S

● Featured grade 主推牌号 ○ Optional grade 可选牌号


W 外螺纹



Inserts shape	Type	Pitch Range (TPI)	Dimensions(mm)						Coated Cemented Carbide								
			PDY	PDX	RE	IC	S	D1	JE7015P	JE7025P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
	16ERM11W-HGA	11	1.2	1.5	0.30	9.525	3.47	4	○	●	○	●	○	○	●	○	●
	16ERM14W-HGA	14	1.2	1.5	0.24	9.525	3.47	4	○	●	○	●	○	○	●	○	●

● Featured grade 主推牌号 ○ Optional grade 可选牌号


ISO公制 内螺纹



Inserts shape	Type	Pitch Range (mm)	Dimensions(mm)						Coated Cemented Carbide								
			PDY	PDX	RE	IC	S	D1	JE7015P	JE7025P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
	11IRM1.00ISO-HGB	1.00	0.8	0.7	0.07	6.35	3.00	3.2	○	●	○	●	○	○	●	○	●
	16IRM150ISO-HGB	1.50	0.8	1.0	0.11	9.525	3.47	4	○	●	○	●	○	○	●	○	●
	16IRM200ISO-HGB	2.00	1.2	1.3	0.15	9.525	3.47	4	○	●	○	●	○	○	●	○	●
	16IRM250ISO-HGB	2.50	1.2	1.5	0.18	9.525	3.47	4	○	●	○	●	○	○	●	○	●
	16IRM300ISO-HGB	3.00	1.2	1.5	0.22	9.525	3.47	4	○	●	○	●	○	○	●	○	●

● Featured grade 主推牌号 ○ Optional grade 可选牌号


W 内螺纹



Inserts shape	Type	Pitch Range (TPI)	Dimensions(mm)						Coated Cemented Carbide								
			PDY	PDX	RE	IC	S	D1	JE7015P	JE7025P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
	16IRM11W-HGA	11	1.2	1.5	0.30	9.525	3.47	4	○	●	○	●	○	○	●	○	●
	16IRM14W-HGA	14	1.2	1.5	0.24	9.525	3.47	4	○	●	○	●	○	○	●	○	●

● Featured grade 主推牌号 ○ Optional grade 可选牌号


NPT 外螺纹



Inserts shape	Type	Pitch Range (TPI)	Dimensions(mm)						Coated Cemented Carbide								
			PDY	PDX	RE	IC	S	D1	JE7015P	JE7025P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
	16ERM11.5NPT-HGB	11.5	1.2	1.5	0.25	9.525	3.47	4	○	●	○	●	○	○	●	○	●
	16ERM14NPT-HGB	14	1.2	1.5	0.22	9.525	3.47	4	○	●	○	●	○	○	●	○	●

● Featured grade 主推牌号 ○ Optional grade 可选牌号


BSPT 外螺纹



Inserts shape	Type	Pitch Range (TPI)	Dimensions(mm)						Coated Cemented Carbide								
			PDY	PDX	RE	IC	S	D1	JE7015P	JE7025P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
	16ERM11BSPT-HGB	11	1.2	1.5	0.30	9.525	3.47	4	○	●	○	●	○	○	●	○	●
	16ERM14BSPT-HGB	14	1.2	1.5	0.24	9.525	3.47	4	○	●	○	●	○	○	●	○	●

● Featured grade 主推牌号 ○ Optional grade 可选牌号


NPT 内螺纹



Inserts shape	Type	Pitch Range (TPI)	Dimensions(mm)						Coated Cemented Carbide								
			PDY	PDX	RE	IC	S	D1	JE7015P	JE7025P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
	16IRM11.5NPT-HGB	11.5	1.2	1.5	0.25	9.525	3.47	4	○	●	○	●	○	○	●	○	●
	16IRM14NPT-HGB	14	1.2	1.5	0.22	9.525	3.47	4	○	●	○	●	○	○	●	○	●

● Featured grade 主推牌号 ○ Optional grade 可选牌号


BSPT 内螺纹



Inserts shape	Type	Pitch Range (TPI)	Dimensions(mm)						Coated Cemented Carbide								
			PDY	PDX	RE	IC	S	D1	JE7015P	JE7025P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
	16IRM11BSPT-HGB	11	1.2	1.5	0.30	9.525	3.47	4	○	●	○	●	○	○	●	○	●
	16IRM14BSPT-HGB	14	1.2	1.5	0.24	9.525	3.47	4	○	●	○	●	○	○	●	○	●

● Featured grade 主推牌号 ○ Optional grade 可选牌号


NPT 外螺纹



Inserts shape	Type	Pitch Range (TPI)	Dimensions(mm)						Coated Cemented Carbide								
			PDY	PDX	RE	IC	S	D1	JE7015P	JE7025P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
	16ERM11.5NPT-HGB	11.5	1.2	1.5	0.25	9.525	3.47	4	○	●	○	●	○	○	●	○	●
	16ERM14NPT-HGB	14	1.2	1.5	0.22	9.525	3.47	4	○	●	○	●	○	○	●	○	●

● Featured grade 主推牌号 ○ Optional grade 可选牌号


BSPT 外螺纹



Inserts shape	Type	Pitch Range (TPI)	Dimensions(mm)						Coated Cemented Carbide								
			PDY	PDX	RE	IC	S	D1	JE7015P	JE7025P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
	16ERM11BSPT-HGB	11	1.2	1.5	0.30	9.525	3.47	4	○	●	○	●	○	○	●	○	●
	16ERM14BSPT-HGB	14	1.2	1.5	0.24	9.525	3.47	4	○	●	○	●	○	○	●	○	●

● Featured grade 主推牌号 ○ Optional grade 可选牌号


NPT 内螺纹



Inserts shape	Type	Pitch Range (TPI)	Dimensions(mm)						Coated Cemented Carbide								
			PDY	PDX	RE	IC	S	D1	JE7015P	JE7025P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
	16IRM11.5NPT-HGB	11.5	1.2	1.5	0.25	9.525	3.47	4	○	●	○	●	○	○	●	○	●
	16IRM14NPT-HGB	14	1.2	1.5	0.22	9.525	3.47	4	○	●	○	●	○	○	●	○	●

● Featured grade 主推牌号 ○ Optional grade 可选牌号

BSPT 内螺纹





Inserts shape	Type	Pitch Range (TPI)	Dimensions(mm)						Coated Cemented Carbide								
			PDY	PDX	RE	IC	S	D1	JE7015P	JE7025P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
	16IRM11BSPT-HGB	11	1.2	1.5	0.30	9.525	3.47	4	○	●	○	●	○	○	●	○	●
	16IRM14BSPT-	14	1.2	1.5	0.24	9.525	3.47	4	○	●	○	●	○	○	●	○	●

● Featured grade 主推牌号 ○ Optional grade 可选牌号

切槽刀





KNMR□□

																	
Inserts shape	Type	Dimensions(mm)						Grooving Inserts Recommended Grade									
		T		L		W	JE7015P	JE7025P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S		
	KNMR1104L	4.19		14.43		5.94	○	●	○	●	○	○	●	○	●		
	KNMR1104R	4.19		14.43		5.94	○	●	○	●	○	○	●	○	●		
	KNMR2005L	5.33		24.26		9.19	○	●	○	●	○	○	●	○	●		
	KNMR2005R	5.33		24.26		9.19	○	●	○	●	○	○	●	○	●		
	KNMR2406L	6.93		29.9		12.01	○	●	○	●	○	○	●	○	●		
	KNMR2406R	6.93		29.88		12.01	○	●	○	●	○	○	●	○	●		
	KNMR2410L	10.16		29.78		12.01	○	●	○	●	○	○	●	○	●		
	KNMR2410R	10.16		29.78		12.01	○	●	○	●	○	○	●	○	●		
	KNMR3510L	10.16		41.61		17.86	○	●	○	●	○	○	●	○	●		
	KNMR3510R	10.16		41.61		17.86	○	●	○	●	○	○	●	○	●		
	KNMR3513L	13.0		41.61		17.86	○	●	○	●	○	○	●	○	●		
	KNMR3513R	13.0		41.61		17.86	○	●	○	●	○	○	●	○	●		

● Featured grade 主推牌号 ○ Optional grade 可选牌号



浅槽刀

TGF□□

															
Inserts shape	Type	Dimensions(mm)				Recommended Grade									
		L	W	G	d	t	JE7015P	JE7025P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
	TGF32	16		2.8	3/8	3.18	○	●	○	●	○	○	●	○	●
	TGF32R	16		2.8	3/8	3.18	○	●	○	●	○	○	●	○	●
	TGF32L	16		2.8	3/8	3.18	○	●	○	●	○	○	●	○	●

● Featured grade 主推牌号 ○ Optional grade 可选牌号

GBA□□

							Workpiece material P Steel M Stainless steel K Cast iron N Non-ferrous metal S Heat resistant alloy Ti alloy 连续切削 Continuous cutting 一般工况 General cutting 断续切削 interrupted cutting <table><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>																													
Inserts shape	Type	Dimensions(mm)					Recommended Grade																													
		L	W	G	d	t	JE7015P	JE7025P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S																					
	GBA43R	22		2.6	3/8	3.18	○	●	○	●	○	○	●	○	●																					
	GBA43L	22		2.6	3/8	3.18	○	●	○	●	○	○	●	○	●																					

● Featured grade 主推牌号 ○ Optional grade 可选牌号

ISO铣削刀片型号表示规则

代号	形状	刀尖角(度)	图形	代号	后角(度)	代号	公差 (mm)			公差 (inch)		
							刀尖高 (m)	厚度 (s)	内切圆 (Ød)	刀尖高 (m)	厚度 (s)	内切圆 (Ød)
H	正六边形	120°		A	3°	A	±0.005	±0.025	±0.025	±0.0002	±0.001	±0.001
O	正八边形	135°		B	5°	F	±0.005	±0.025	±0.013	±0.0002	±0.001	±0.0005
P	正五边形	108°		C	7°	C	±0.013	±0.025	±0.025	±0.0005	±0.001	±0.001
S	正方形	90°		D	15°	H	±0.013	±0.025	±0.013	±0.0005	±0.001	±0.0005
T	正三角形	60°		E	20°	E	±0.025	±0.025	±0.025	±0.001	±0.001	±0.001
C	菱形	80°		F	25°	G	±0.025	±0.13	±0.025	±0.001	±0.005	±0.001
D		55°		G	30°	J	±0.005	±0.025	±0.05~±0.13	±0.0002	±0.001	±0.002~±0.005
E		75°		N	0°	K	±0.013	±0.025	±0.05~±0.13	±0.0005	±0.001	±0.002~±0.005
F		50°		O	其他	L	±0.025	±0.025	±0.05~±0.13	±0.001	±0.001	±0.002~±0.005
M		86°					M	±0.08~±0.18	±0.13	±0.05~±0.13	±0.003~±0.007	±0.005
V	35°	35°					N	±0.08~±0.18	±0.025	±0.05~±0.13	±0.003~±0.007	±0.005
W	六边形	80°		②后角代号			U	±0.13~±0.38	±0.13	±0.08~±0.25	±0.005~±0.015	±0.01
L	长方形	90°					③精度代号					
A	平行 四边形	85°		①形状代号								
B		82°										
K		55°										
R	圆形	—										

①

②

③

④

⑤

S
R

N
D

E
E

U
T

12
12

①

②

③

④

⑤

④断屑槽·孔代号					⑤ISO切削刃长度代号 (mm)																
代号	有无孔	孔的形状	断屑槽	形状									内切圆 (mm)								
N	无	—	无		代号	尺寸	代号	尺寸	代号	尺寸	代号	尺寸	代号	尺寸	代号	尺寸					
R			单面			03	3.97	03	4.0		06	6.9	4	4.8			3.97				
F			双面			04	4.76	04	4.8		08	8.2	5	5.8			4.76				
A	有	圆柱孔	无		05	5	—	—	—	—	—	—	—	—	—	—	5				
M			单面		05	5.56	05	5.6	03	3.8	09	9.6	6	6.8			5.56				
G			双面		06	6	—	—	—	—	—	—	—	—	—	—	6				
W				06	6.35	06	6.5	04	4.3	11	11	7	7.8	11	11.2		6.35				
T		部分圆柱孔单面 40°~60°	无		07	7.94	08	8.1	05	5.4	13	13.8	9	9.7			7.94				
Q			单面		08	8	—	—	—	—	—	—	—	—	—	—	8				
U		部分圆柱孔双 面40°~60°	无		09	9.525	09	9.525	09	9.7	06	6.5	16	16.5	11	11.6	16	16.6	16	19.7	9.525
B			双面		10	10	—	—	—	—	—	—	—	—	—	—	—	—	—	10	
H		部分圆柱孔单面 70°~90°	无		12	12	—	—	—	—	—	—	—	—	—	—	—	—	—	12	
C			单面		12	12.7	12	12.7	12	12.9	08	8.7	22	22	15	15.5	22	22.1		12.7	
J		部分圆柱孔双 面70°~90°	双面		15	15.875	15	15.875	16	16.1	10	10.9	27	27.5	19	19.4				15.875	
X					—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	16	
							19	19.05	19	19.05	19	19.3	13	13	33	33	23	23.3			19.05
							20	20	—	—	—	—	—	—	—	—	—	—	—	—	20
						22	22.225	22	22.6			38	38.5	27	27.1				22.225		
					25	25	—	—	—	—	—	—	—	—	—	—	—	—	25		
					25	25.4	25	25.4	25	25.8		44	44	31	31				25.4		
					31	31.75	31	31.75	32	32.2		55	55	38	38.8				31.75		
					31	32	—	—	—	—	—	—	—	—	—	—	—	—	32		

适用刀片形状：H,O,P,S,T,C,E,M,W,R											
标准 内切圆 (mm)	内切圆(Ød)的公差 (mm)		刀尖高(m)的公差 (mm)		标准 内切圆 (inch)	内切圆(Ød)的公差 (inch)		刀尖高(m)的公差 (inch)		标准 内切圆 (mm)	厚度 (mm)
	J,K,L, M,N(级)	U (级)	M,N(级)	U (级)		Class J,K, L,M,N	Class U	Class J,K, L,M,N	Class U		
6.35	±0.05	±0.08	±0.08	±0.13	0.250	±0.002	±0.003	±0.003	±0.005	0.250	0.159
9.525	±0.05	±0.08	±0.08	±0.13	0.375	±0.002	±0.003	±0.003	±0.005	0.375	1.98
12.7	±0.08	±0.13	±0.13	±0.2	0.500	±0.003	±0.005	±0.005	±0.008	0.500	2.38
15.875	±0.1	±0.18	±0.15	±0.27	0.625	±0.004	±0.007	±0.006	±0.011	0.625	2.78
19.05	±0.13	±0.25	±0.18	±0.38	0.750	±0.005	±0.010	±0.007	±0.015	0.750	3.18
25.4	±0.15	±0.25	±0.2	±0.38	1.000	±0.006	±0.010	±0.008	±0.015	1.000	3.97
31.75	±0.15	±0.25	±0.2	±0.38	1.250	±0.006	±0.010	±0.008	±0.015	1.250	4.76
32	±0.15	±0.25	±0.2	±0.38	1.260	±0.006	±0.010	±0.008	±0.015	1.260	5.56

适用刀片形状：D						适用刀片形状：V					
内切圆(Ød)		内切圆的公差		刀尖高的公差		内切圆(Ød)		内切圆的公差		刀尖高的公差	
mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch
6.35	0.250	±0.05	±0.002	±0.11	±0.004	6.35	0.250	±0.05	±0.002	±0.15	±0.006
9.525	0.375	±0.05	±0.002	±0.11	±0.004	9.525	0.375	±0.05	±0.002	±0.15	±0.006
12.7	0.500	±0.08	±0.003	±0.15	±0.006	12.7	0.500	±0.08	±0.003	±0.20	±0.008
15.875	0.625	±0.10	±0.004	±0.18	±0.007	15.875	0.625	±0.10	±0.004	±0.27	±0.011
19.05	0.750	±0.10	±0.004	±0.18	±0.007	19.05	0.750	±0.10	±0.004	±0.27	±0.011

代号	厚度 (mm)
01	1.59
T1	1.98
02	2.38
T2	2.78
03	3.18
T3	3.97
04	4.76
05	5.56
06	6.35
07	7.94
09	9.52
⑥厚度代号	

⑥

⑦

⑧

⑨

⑩

06
04

AN
MO

E
T

N
—

GM
MM

⑥

⑦

⑧

⑨


⑩

内切圆(Ød)	⑦主偏角、修光刃后角及刀尖形状						⑧主切削刃代号			⑩断屑槽代号
刀尖高(m)							代号	切削刃形状	形状	
刀片厚度(s)										
	余偏角		主偏角		后角		圆弧半径		F	锋利刃
	代号	余偏角	主偏角	代号	修光刃后角	代号	刀尖圆弧半径(mm)	圆刀片	E	圆弧刃
	A	45°	45°	A	3°	M0	0.03	圆刀片	T	负倒棱角
	D	30°	60°	B	5°	00	0.03	圆刀片	S	复合钝化刃
	E	15°	75°	C	7°	02	0.2	圆刀片		
	F	5°	85°	D	15°	04	0.4	圆刀片		
	P	0°	90°	E	20°	08	0.8	圆刀片		
	Z	其他		F	25°	12	1.2	圆刀片		
				G	30°	16	1.6	圆刀片		
						N	0°	20	2.0	
						P	11°	24	2.4	
						Z	其他	28	2.8	
								32	3.2	

⑨切削方向代号		
代号	切削刃形状	图示
R	右	
L	左	
N	无	


■ 方肩铣削

AP□□

		连续切削 Continuous cutting 一般工况 General cutting 断续切削 Interrupted cutting															
		Workpiece material P Steel M Stainless steel K Cast iron N Non-ferrous metal S Heat resistant alloy Ti alloy															
Inserts shape	Type	Dimensions (mm)					Coating/Grade										
		I.W	L	S	d	r	CVD				PVD			CVD		PVD	
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
	APKT170508R-MGB	10.74	18.44	5.56	4.5	0.8	○	○	●	○	○	●	○	○	●	○	●
	APKT170516R-MGB	10.74	18.44	5.56	4.5	1.6	○	○	●	○	○	●	○	○	●	○	●
	APKT170524R-MGB	10.74	18.44	5.56	4.5	2.4	○	○	●	○	○	●	○	○	●	○	●
	APKT170530R-MGB	10.74	18.3	5.56	4.5	3	○	○	●	○	○	●	○	○	●	○	●
	APKT170540R-MGB	10.74	16.84	5.56	4.5	4	○	○	●	○	○	●	○	○	●	○	●
	APMT1135PDER-MGF	6.16	10.83	3.18	2.8	0.8	○	○	●	○							
	APMT1604PDER-MGF	9.25	16.26	4.76	4.4	0.8	○	○	●	○							
	APMT1135PDER-MRA	6.16	10.83	3.18	2.8	0.8	○	○	●	○							
	APMT1604PDER-MRA	9.25	16.26	4.76	4.4	0.8	○	○	●	○							
	APMT1135PDER-MRB	6.16	10.83	3.18	2.8	0.8	○	○	●	○							
	APMT1604PDER-MRB	9.26	16.26	4.76	4.4	0.8	○	○	●	○							


● Featured grade 主推牌号 ○ Optional grade 可选牌号

3P□□

		连续切削 Continuous cutting 一般工况 General cutting 断续切削 Interrupted cutting															
		Workpiece material P Steel M Stainless steel K Cast iron N Non-ferrous metal S Heat resistant alloy Ti alloy															
Inserts shape	Type	Dimensions(mm)					Coating/Grade										
		I.C	L	S	d	r	CVD				PVD		CVD		PVD		
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
	3PKT100408R-MGC	6.9	10.5	4.0	3.25	0.8	○	○	●	○	○	●	○	○	●	○	●
	3PKT150508R-MGC	10.7	15.5	5.0	4.75	0.8	○	○	●	○	○	●	○	○	●	○	●

● Featured grade 主推牌号 ○ Optional grade 可选牌号

4N□□


						连续切削 Continuous cutting 一般工况 General cutting 断续切削 Interrupted cutting											
Workpiece material P Steel M Stainless steel K Cast iron N Non-ferrous metal S Heat resistant alloy Ti alloy																	
Inserts shape	Type	Dimensions(mm)					Coating/Grade										
		I.C	L	S	d	r	CVD				PVD		CVD		PVD		
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
	4NKT060308R-MGC	6.6	6.6	3.71	3.4	0.8	○	○	●	○	○	●	○	●	○	●	

● Featured grade 主推牌号 ○ Optional grade 可选牌号


■ 方肩铣削

LN□□


LO□□

		连续切削 Continuous cutting 一般工况 General cutting 断续切削 Interrupted cutting													
Workpiece material P Steel M Stainless steel K Cast iron N Non-ferrous metal S Heat resistant alloy Ti alloy															
Inserts shape	Type	Dimensions(mm)					Coating/Grade								
		I.W	L	T	d	r	CVD				PVD				
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K
	LNMU15T608SRGE	10	16.15	6.95	4.65	0.8	○	○	●	○	○	●	○	○	●
	LNMU0303ZER	6.0	11.6	3.7	3.2	2	○	○	●	○					
	LNMU110408SRGE	6.6	11.3	4.83	3.4	0.8	○	○	●	○	○	●	○	○	●
	LORU030310ER-MGA	6.2	11.96	3.96	3.45	2	○	○	●	○					

BDMT□□



		连续切削 Continuous cutting 一般工况 General cutting 断续切削 Interrupted cutting													
Workpiece material P Steel M Stainless steel K Cast iron N Non-ferrous metal S Heat resistant alloy Ti alloy															
Inserts shape	Type	Dimensions(mm)					Coating/Grade								
		I.C	L	S	d	r	CVD				PVD				
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K
	BDMT11T308ER-MGL	6.95	12.15	3.8	2.8	0.8	○	○	●	○					

JDMT□□

		连续切削 Continuous cutting 一般工况 General cutting 断续切削 Interrupted cutting													
Workpiece material P Steel M Stainless steel K Cast iron N Non-ferrous metal S Heat resistant alloy Ti alloy															
Inserts shape	Type	Dimensions(mm)					Coating/Grade								
		I.W	L	S	d	r	CVD				PVD				
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K
	JDMT070204R	4.25	7.05	2.45	1.95	0.4	○	○	●	○					
	JDMT070208R	4.25	7.05	2.45	1.95	0.8	○	○	●	○					

● Featured grade 主推牌号 ○ Optional grade 可选牌号

XOMX□□

		连续切削 Continuous cutting 一般工况 General cutting 断续切削 Interrupted cutting															
Workpiece material P Steel M Stainless steel K Cast iron N Non-ferrous metal S Heat resistant alloy Ti alloy																	
Inserts shape	Type	Dimensions(mm)						Coating/Grade									
		I.W	L	S	d	r	CVD				PVD						
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
	XOMX120408TR-MGE	8.2	14.6	5.07	3.9	0.8	○	○	●	○	○	●	○	○	●	○	●
	XOMX120420TR-MGE	8.2	13.7	5.07	3.9	2	○	○	●	○	○	●	○	○	●	○	●
	XOMX120440TR-MGE	8.2	13.1	5.07	3.9	4	○	○	●	○	○	●	○	○	●	○	●
	XOMX060204R-MGG	4.06	6.9	2.45	1.95	0.8	○	○	●	○							
	XOMX060208R-MGG	4.06	6.9	2.45	1.95	0.8	○	○	●	○							

● Featured grade 主推牌号 ○ Optional grade 可选牌号

仿形铣削 & 圆刀片铣削



Inserts shape	Type	Dimensions(mm)					Coating/Grade									
		I.W	L	S	d	r	CVD					PVD				
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S
	RDET10T3MOT	10.0	10.0	3.97	4.4		○	○	●	○						
	RDET1204MOT	12.0	12.0	4.76	4.4		○	○	●	○						
	RDMT10T3M0	10.0	10.0	3.97	4.4		○	○	●	○						
	RDMT1604MO	16.0	16.0	4.76	5.5		○	○	●	○						
	RDMW1204M0T-MGH	12.0	12.0	4.76	4.4		○	○	●	○						
	RDMW10T3M0	10.0	10.0	3.97	4.4		○	○	●	○						
	RDMW1204MOT	12.0	12.0	4.76	4.4		○	○	●	○						
	RDMW1605M0T	16.0	16.0	5.56	5.5		○	○	●	○						
	RDMW1204M0T-MRB	12.0	12.0	4.76	4.4		○	○	●	○						

● Featured grade 主推牌号 ○ Optional grade 可选牌号



Inserts shape	Type	Dimensions(mm)					Coating/Grade									
		I.W	L	S	d	r	CVD					PVD				
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S
	RPET1204MO-MAA	12.0	12.0	4.76	4.4		○	○	●	○						
	RPMT10T3MOE-MGI	10.0	10.0	3.18	4.4		○	○	●	○						
	RPMT1204MO-MRA	12.0	12.0	4.76	4.4		○	○	●	○						
	RPMW08T2M0A-MGA	8.0	8.0	2.78	3.08		○	○	●	○						
	RPMW1003M0	10.0	10.0	3.18	4.4		○	○	●	○						
	RPMW1204M0	12.0	12.0	4.76	4.4		○	○	●	○						
	RPMW1003MO-MRA	12.0	12.0	4.76	4.4		○	○	●	○						

● Featured grade 主推牌号 ○ Optional grade 可选牌号

面铣 & 双面铣削

ON□□

		连续切削 Continuous cutting 一般工况 General cutting 断续切削 Interrupted cutting <table><tr><td>P Steel</td><td>●</td><td>●</td><td>●</td><td>●</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>M Stainless steel</td><td></td><td></td><td></td><td></td><td>●</td><td>●</td><td>●</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>K Cast iron</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>●</td><td>●</td><td></td><td></td><td></td></tr><tr><td>N Non-ferrous metal</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>S Heat resistant alloy Ti alloy</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>●</td><td>●</td><td></td></tr></table>												P Steel	●	●	●	●									M Stainless steel					●	●	●						K Cast iron								●	●				N Non-ferrous metal													S Heat resistant alloy Ti alloy										●	●	
P Steel	●	●	●	●																																																																										
M Stainless steel					●	●	●																																																																							
K Cast iron								●	●																																																																					
N Non-ferrous metal																																																																														
S Heat resistant alloy Ti alloy										●	●																																																																			
Inserts shape	Type	Dimensions(mm)					Coating/Grade																																																																							
		I.C	L	S	d	r	CVD				PVD																																																																			
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S																																																													
	ONMU050608	13.4		5.88	4.68	0.8	○	○	●	○																																																																				
	ONRG060407ANEN	13.5		5.38	2.0	0.7	○	○	●	○	○	●	○	○	●	○	●																																																													

● Featured grade 主推牌号

○ Optional grade 可选牌号

OD□□

OE□□

OP□□

							连续切削 Continuous cutting 一般工况 General cutting 断续切削 Interrupted cutting <table><tr><td rowspan="5">Workpiece material</td><td>P Steel</td><td> </td><td> </td><td> </td><td> </td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>M Stainless steel</td><td></td><td></td><td></td><td></td><td> </td><td> </td><td> </td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>K Cast iron</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td> </td><td> </td><td></td><td></td><td></td><td></td></tr><tr><td>N Non-ferrous metal</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>S Heat resistant alloy Ti alloy</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td> </td><td> </td><td></td></tr></table>												Workpiece material	P Steel																M Stainless steel																K Cast iron																N Non-ferrous metal																S Heat resistant alloy Ti alloy															
Workpiece material	P Steel																																																																																																		
	M Stainless steel																																																																																																		
	K Cast iron																																																																																																		
	N Non-ferrous metal																																																																																																		
	S Heat resistant alloy Ti alloy																																																																																																		
Inserts shape	Type	Dimensions(mm)					Coating/Grade																																																																																												
		I.C	L	S	d	r	CVD				PVD			CVD		PVD																																																																																			
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S																																																																																		
	ODRT040404	12.7		4.76	4.7	0.4	○	○	●	○	○	●	○	○	●	○	●																																																																																		
	ODRT090308	9.525		3.18	3.56	0.8	○	○	●	○	○	●	○	○	●	○	●																																																																																		
	OERW060400	14.29		4.76	4.75		○	○	●	○	○	●	○	○	●	○	●																																																																																		
	OPRT160512	15.875		5.56	5.59	1.2	○	○	●	○	○	●	○	○	●	○	●																																																																																		

HD□□

		连续切削 Continuous cutting 一般工况 General cutting 断续切削 Interrupted cutting															
Workpiece material	P Steel	●	●	●	●												
	M Stainless steel						●	●	●								
	K Cast iron										●	●					
	N Non-ferrous metal																
	S Heat resistant alloy Ti alloy													●	●		
Inserts shape	Type	Dimensions(mm)					Coating/Grade										
		I.C	L	T	d	r	CVD				PVD						
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
	HDMX070408MM	12.7		4.76	4.5	0.8	○	○	●	○	○	●	○	○	●	○	●


● Featured grade 主推牌号

○ Optional grade 可选牌号

JE8015P
JE8020P
JE8025P
JE8035P
JE6015M
JE6025M
JE6035M
JE4015K
JE4025K
JE5015S
JE5025S

高进给铣削

SDMT□□



连续切削
Continuous cutting

一般工况
General cutting

断续切削
Interrupted cutting


P Steel

M Stainless steel

K Cast iron

N Non-ferrous metal


S Heat resistant alloy Ti alloy

Inserts shape	Type	Dimensions(mm)					Coating/Grade							
		I.C	L	S	d	r	CVD				PVD			
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K
	SDMT120512	12.7		5.56	1.2		○	○	●	○	○	●	○	●
	SDMT150512	15.875		5.56	1.2		○	○	●	○	○	●	○	●

● Featured grade
主推牌号

○ Optional grade
可选牌号

PNMU□□



连续切削
Continuous cutting

一般工况
General cutting

断续切削
Interrupted cutting


P Steel

M Stainless steel

K Cast iron

N Non-ferrous metal


S Heat resistant alloy Ti alloy

Inserts shape	Type	Dimensions(mm)					Coating/Grade							
		I.C	L	S	d	r	CVD				PVD			
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K
	PNMU0905XNER-MGA	13.5		5.56	4.7	0.8	○	○	●	○	○	●	○	●

● Featured grade
主推牌号

○ Optional grade
可选牌号

WNMU□□



连续切削
Continuous cutting

一般工况
General cutting

断续切削
Interrupted cutting


P Steel

M Stainless steel

K Cast iron

N Non-ferrous metal


S Heat resistant alloy Ti alloy

Inserts shape	Type	Dimensions(mm)					Coating/Grade							
		I.C	L	S	d	r	CVD				PVD			
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K
	WNMU080608EN-MGA	14		8.3	6.2	0.8	○	○	●	○	○	●	○	●

● Featured grade
主推牌号

○ Optional grade
可选牌号

BLMP□□



连续切削
Continuous cutting

一般工况
General cutting

断续切削
Interrupted cutting

P Steel

M Stainless steel

K Cast iron

N Non-ferrous metal

S Heat resistant alloy Ti alloy



Inserts shape	Type	Dimensions(mm)					Coating/Grade							
		I.C	L	S	d	r	CVD				PVD			
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K
	BLMP0603R-MGC	6.22	9	3.37	3.15	6	○	○	●	○	○	●	○	●
	BLMP0603R-MGJ	6.22	9	3.37	3.2	6	○	○	●	○	○	●	○	●

● Featured grade
主推牌号

○ Optional grade
可选牌号

高进给铣削

ENMU□□

				连续切削 Continuous cutting 一般工况 General cutting 断续切削 Interrupted cutting													
Workpiece material		P Steel															
		M Stainless steel															
		K Cast iron															
		N Non-ferrous metal															
		S Heat resistant alloy Ti alloy															
Inserts shape	Type	Dimensions(mm)					Coating/Grade										
		I.W	L	T	d	r	CVD				PVD			CVD		PVD	
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
	ENMU100412PER-MGK	6	10	3.6	3	1.2	○	○	●	○	○	●	○	○	●	○	●

● Featured grade 主推牌号
○ Optional grade 可选牌号

端铣 & 周边铣削

LNMC□□

				连续切削 Continuous cutting 一般工况 General cutting 断续切削 Interrupted cutting													
				Workpiece material P Steel M Stainless steel K Cast iron N Non-ferrous metal S Heat resistant alloy Ti alloy													
Inserts shape	Type	Dimensions(mm)					Coating/Grade										
		I.W	L	S	d	r	CVD				PVD						
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K	JE4025K	JE5015S	JE5025S
	LNMC120500	12.7	12.7	5.56	4.5									○	●		
	LNMC130600	12.7	12.7	6.35	5.2									○	●		
	LNMC150600	12.7	15.875	7.94	5.6									○	●		
	LNMC150700	15.88	15.875	7.94	5.6									○	●		
	LNMC190602	14.3	19.05	6.35	5.8									○	●		
	LNMC250500	14.3	25.4	4.76	5.4									○	●		
	LNMC251200	15.88	25.4	12.7	6.5									○	●		
	LNMC270902	15.6	27.9	9.52	5.7									○	●		
	LNMC280500	15.0	28.8	4.76	5.7		○	○	●	○	○	●	○	○	●	○	●

● Featured grade 主推牌号
○ Optional grade 可选牌号

端铣 & 周边铣削

SNHX

连续切削 Continuous cutting

一般工况 General cutting

断续切削 Interrupted cutting

Workpiece material

- P Steel
- M Stainless steel
- K Cast iron
- N Non-ferrous metal
- S Heat resistant alloy Ti alloy

Inserts shape	Type	Dimensions(mm)					Coating/Grade							
		I.W	L	S	d	r	CVD				PVD			
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K
	SNHX-11	11		2.7	4									
	SNHX-13	13		3.2	5									
	SNHX-16	16		4.2	5									
	SNHX-17	17		4.2	5									
	SNHX-20	20		5.2	6									
	SNHX-25	25		6.2	6									
	SNHX-26	26		6.2	6									
	SNHX-30	30		7.2	8									

Featured grade 主推牌号

Optional grade 可选牌号

木工铣削 & 特殊铣削

LOMB

连续切削 Continuous cutting

一般工况 General cutting

断续切削 Interrupted cutting

Workpiece material

- P Steel
- M Stainless steel
- K Cast iron
- N Non-ferrous metal
- S Heat resistant alloy Ti alloy

Inserts shape	Type	Dimensions(mm)					Coating/Grade							
		I.C	L	T	d	r	CVD				PVD			
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K
	LOMB300200	12.0	30.0	1.5										

Featured grade 主推牌号

Optional grade 可选牌号

SGMB

连续切削 Continuous cutting

一般工况 General cutting

断续切削 Interrupted cutting

Workpiece material

- P Steel
- M Stainless steel
- K Cast iron
- N Non-ferrous metal
- S Heat resistant alloy Ti alloy

Inserts shape	Type	Dimensions(mm)					Coating/Grade							
		I.C	L	T	d	r	CVD				PVD			
							JE8015P	JE8020P	JE8025P	JE8035P	JE6015M	JE6025M	JE6035M	JE4015K
	SGMB140200	14.0		2.0	6.4									
	SGMB150250	15.0		2.5	6.5									

Featured grade 主推牌号

Optional grade 可选牌号